716 in white with large TL lites

712 in sahara tan with full view section

716 in sandstone with full view sections

COMMERCIAL 700 SERIES

1¾" Thick **R-16.18**

710 / 712 / 714 / 716 / 732 / 733 / 732-20 / 733-20 / 750 / 751 / 760 / 763 / 764 / 770 / 771 / 772 / 773 / 774 / 780 / 781 / 782 / 790

Built to Last

Haas 700 Series commercial insulated steel doors stand up to the elements, while dramatically decreasing exterior noise and enhancing the overall aesthetics of your building at the same time. The 1¾" thick 700 Series insulated steel doors help increase energy savings with polyurethane foam cores and are built to last.

716 with pass door

700 QUICK GUIDE

Model	Door Thickness	R-Value*	Max. Door Size		End Stile Type	Section Skins	
			Width	Height		Inside	Outside
710	1-3/4" (44.5mm)	16.18	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
712	1-3/4" (44.5mm)	16.18	18'-2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
714	1-3/4" (44.5mm)	16.18	38'-2"	32'-0"	Steel	26 GA V-Groove Woodgrain Steel	26 GA Flush Woodgrain Steel
716	1-3/4" (44.5mm)	16.18	38'-2"	32'-0"	Steel	26 GA V-Groove Woodgrain Steel	26 GA V-Groove Woodgrain Steel
732	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Steel	26 GA V-Groove Woodgrain Steel	20 GA Flush Smooth Steel
733	1-3/4" (44.5mm)	16.18	38'-2"	32'-0"	Steel	26 GA V-Groove Woodgrain Steel	20 GA V-Groove Smooth Steel
732-20	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Steel	20 GA V-Groove Smooth Steel	20 GA Flush Smooth Steel
733-20	1-3/4" (44.5mm)	16.18	38'-2"	32'-0"	Steel	20 GA V-Groove Smooth Steel	20 GA V-Groove Smooth Steel
750	1-3/4" (44.5mm)	16.18	38'-2"	32'-0"	Steel	24 GA V-Groove Stucco Aluminum	24 GA V-Groove Stucco Aluminum
751	1-3/4" (44.5mm)	16.18	38'-2"	32'-0"	Steel	24 GA V-Groove Stucco Aluminum	24 GA Flush Stucco Aluminum
760, 772, 782	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Short Panel Woodgrain Steel
761, 771, 781	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Short Panel Woodgrain Steel
763, 773	1-3/4" (44.5mm)	16.18	18-'2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Recessed Long Panel Woodgrain Steel
764, 774	1-3/4" (44.5mm)	16.18	18-'2"	16'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ribbed Long Panel Woodgrain Steel
770	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Ranch Panel Woodgrain Steel
780	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Raised Panel Woodgrain Steel
790	1-3/4" (44.5mm)	16.18	24-'2"	32'-0"	Extruded End Cap	26 GA V-Groove Woodgrain Steel	26 GA Sculptured Panel Woodgrain Steel

*calculated R-Value

Note: Certain weights and/or applications may limit the size allowed

700 DOOR PANELS

Flush Woodgrain
All colors except Bi-Directionals
Model 710 Window Options: p 28-31
Model 714 Window Options: p 31



V-Groove Woodgrain
All colors except Bi-Directionals
Model 712 Window Options: p 31
Model 716 Window Options: p 31



Flush Smooth
Polar White and Brown
Model 732 Window Options: p 31
Model 732-20 Window Options: p 31



V-Groove Smooth
Polar White and Brown
Model 733 Window Options: p 31
Model 733-20 Window Options: p 31



V-Groove Stucco Aluminum
Trinar® Polar White and Trinar® Almond
Model 750 Window Options: p 31



Flush Stucco Aluminum
Trinar® Polar White and Trinar® Almond
Model 751 Window Options: p 31

Ribbed Short Woodgrain Panel
All Colors
Model 760 Window Options: p 29
Model 772 Window Options: p 30
Model 782 Window Options: p 28



Recessed Short Woodgrain Panel
All Colors
Model 761 Window Options: p 29
Model 771 Window Options: p 30
Model 781 Window Options: p 28



Ribbed Long Woodgrain Panel
All Colors
Model 764 Window Options: p 29
Model 774 Window Options: p 30



Recessed Long Woodgrain Panel
All Colors
Model 763 Window Options: p 29
Model 773 Window Options: p 30



Ranch Woodgrain Panel
All Colors
Model 770 Window Options: p 30

Raised Standard Woodgrain Panel
All Colors
Model 780 Window Options: p 28

Sculptured Raised Woodgrain Panel
All Colors
Model 790 Window Options: p 28

A **Full Thermal Break** is used in the tongue-and-groove construction of all 700 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.



OPTIONS

700 Series Available Options

2" or 3" Track
Double Steel End Stiles
Exhaust Port
Cam Safety Device
Spring Bumpers
Chain Hoist
High Cycle Springs
Glazing (lites)
High Cycle Rollers
Aluminum Full View Section
Pass Door
Top Header Seal
Keyed Lock
Wind Load Rating
ASTM E 84 Fire Rated

Optional Exhaust Port (interior view)

Wind Load

Pass Door (exterior view)